

## INSTRUCTIONS FOR:



## LENS REPLACEMENT

**\*\*CAUTION: DO NOT TOUCH THE BULB OR INNER REFLECTOR.** Doing so may cause damage to the lamp.

1. Slowly unscrew the lens cap in a counter-clockwise direction while at the same time holding the lens down (if yours is still there). This keeps the lens/lamp from twisting in the housing. Be careful not to drop the lens once the cap is removed.
2. Remove the lens gasket (white), lens, and lens O-ring.
3. Place the new O-ring in the groove of the cap, if it will not seat then stretch it a little, by taking it out and lightly tugging on it.
4. Place the new lens over the O-ring. Hold it by the edges so as not to get your fingerprints on the inside.
5. Place the new white gasket on the lens.
6. Grasp the light body, then screw the lens cover on 1/2 turn. Seat the lamp by pushing the lens all the way down and hold it down. Continue to screw on the lens cover (paying special attention to the white lens gasket, making sure it does not spin or get caught in the threads) while holding the lens down, until tight. When all is correct the mounting ring and the lens should not move.
7. You may want to use some "super glue" and reseal the wire grommet to insure water tightness. Remove any old sealer before applying

Note: Weekend Concepts cannot be responsible for any lamp or seal damage that may occur during re-assembly, this includes any subsequent leaking or failure of any component.

If you need any assistance please call us at (562) 634-3783, Monday thru Friday.